Proceedings of CONF-APMM 2025 Symposium: Multi-Qubit Quantum Communication for Image Transmission over Error Prone Channels
DOI: 10.54254/2753-8818/2025.GL25551

Fluid Dynamics in Racing Car Design: A Comprehensive Analysis of Aerodynamic Optimization and Future Trends

Rongzhou Chen

College of Engineering, University of New South Wales, Sydney, Australia
z5679347@ad.unsw.edu.au

Abstract: Fluid mechanics plays a crucial role in the design and optimization of race cars, significantly affecting their aerodynamic performance, stability, and fuel efficiency, all of which directly impact the drivers' final standings. This study explores the application of fluid dynamics in enhancing racing car performance, focusing on drag reduction, downforce optimization, and cooling system efficiency. Through literature review and analysis of recent research indexed in Scopus and Crossref, the study examines advancements in computational fluid dynamics (CFD), wind tunnel testing, and innovative aerodynamic designs. Results indicate that effectively applying fluid mechanics principles can significantly improve racing car competitiveness. The study also discusses future trends, including active aerodynamics and AI optimization, highlighting the potential for further performance gains.

Keywords: Fluid Mechanics, Racing Cars, Turbulence Models, Drag Reduction, Increased Downforce

1. Introduction

In the intensely competitive world of motorsport, aerodynamic performance is paramount, directly influencing a car's speed, stability, and fuel efficiency, ultimately determining race outcomes. As regulations tighten and environmental concerns grow, teams face the dual challenge of maximizing downforce and minimizing drag while exploring energy-efficient designs. This paper addresses critical aerodynamic challenges in racing car design, including drag reduction, downforce optimization for cornering stability, and efficient cooling system integration. To tackle these issues, we review recent advancements leveraging fluid dynamics principles, focusing on computational fluid dynamics (CFD) simulations, topology optimization, and experimental validation through wind tunnel testing. Studies from Scopus, Crossref, Doaj, and ProQuest databases are analyzed, covering topics from boundary layer control and Y250 vortex management to ground effect enhancement and active aerodynamic systems. This research provides valuable insights into how fluid mechanics shapes modern racing technology. By synthesizing these findings, this work offers theoretical guidance and potential research directions for engineers aiming to design faster, more stable, and sustainable racing cars, contributing to both competitive success and the broader automotive industry's sustainable development.

© 2026 The Authors. This is an open access article distributed under the terms of the Creative Commons Attribution License 4.0 (https://creativecommons.org/licenses/by/4.0/).

DOI: 10.54254/2753-8818/2025.GL25551

2. Aerodynamics and drag reduction

Fluid dynamics plays a decisive role in the drag reduction design of racing cars. Recent studies have shown that improving the accuracy of boundary layer separation predictions through enhanced turbulence models and computational fluid dynamics (CFD) techniques can significantly improve drag reduction effects. Uddin proposes an optimized RANS model that can more accurately predict airflow separation, aiding in the design of low-drag car bodies [1]; Peri confirms that topological optimization can reduce the drag of components by 12-15% [2]. Research on drag reduction under special climatic conditions has also made breakthroughs. Uddin mentioned in his study that multiphase flow simulation provides solutions for rain race events by reducing water film resistance through optimized surface textures [1]; Peri explored microscale drag reduction techniques, such as superhydrophobic surfaces [2].

2.1. Front wing design: guiding airflow and reducing turbulence

The front wing of a racing car is a key component of aerodynamic optimization, with its main function being to guide airflow towards the underside of the car body and side pods while reducing turbulence produced by the tires. Studies show that multi-element flap designs can significantly improve the aerodynamic efficiency of the front wing [3].Y250 Vortex Control: Modern F1 race cars generate Y250 vortices through specially shaped front wings, which flow along the car body, helping to seal the edge of the chassis and enhance ground effect [4].Tire Wake Management: Optimizing the design of the front wing end plates can reduce the impact of tire-induced turbulence on subsequent airflow, thereby enhancing overall aerodynamic efficiency [5].Wake Management Techniques:

2.2. Literature focuses on studying the characteristics of racing car wakes

The traditional wake length of racing cars can reach up to 5 times the length of the car (approximately 25m).By optimizing the shapes of the rearview mirrors and roll bars, the turbulence kinetic energy in the core wake region can be reduced by 28%, leading to a 19% increase in aerodynamic efficiency for following cars (data from wind tunnel PIV tests). Recent developments encompass actively controlled rear wing flaps that utilize magnetorheological fluid dampers. These flaps are designed for the real-time prediction of optimal drag reduction strategies, leveraging machine learning. In recent years, surface microstructure technology has shown great potential in drag reduction for racing cars. Wind tunnel experiments confirm that applying a shark skin-inspired micro-grooved structure to the surface of racing cars can reduce surface friction drag by up to 8%. The mechanism of action lies in the groove structure and the disruption of the turbulence breakdown process, where the groove structure (typical size of 50-100μm) can guide the near-wall airflow to form stable longitudinal vortices, which can reduce momentum exchange. The following is the formula for the reduction in friction drag coefficient:

$$\Delta Cf \approx 0.8 \times (h/s) \hat{} 0.5 \quad (1)$$

(where h is the groove height and s is the spacing).

This can help teams achieve optimal conditions by controlling the variables of these two factors when designing micro-structured films for racing cars.

DOI: 10.54254/2753-8818/2025.GL25551

3. Downforce and cornering stability

In high-speed motorsport, optimizing downforce and cornering stability is directly related to the speed and safety of racing through corners. When a racing car passes through a corner with a radius of 100m at a speed of 200km/h:

$$F_c = mv \hat{} 2/r = F_{down} \times \mu \quad (2)$$

where F_c is the centripetal force (N), m is the car weight (approximately 750kg), v is the speed (55.6m/s), r is the turning radius (100m), μ is the tire friction coefficient (approximately 1.7)). Calculations indicate that to maintain a lateral acceleration of 2.5g, a minimum of 18,375 N of downforce is required.

This data explains why modern F1 cars need to generate downforce equivalent to more than three times their weight. Bang provides new insights into ground effect studies [4]. The models mentioned significantly improve the predictive accuracy of airflow behavior beneath racing cars, enabling engineers to more accurately optimize diffuser designs to enhance downforce generated by ground effect. Research in the literature [2] shows that CFD-assisted topology optimization can enhance the downforce efficiency of front and rear wings by 15-20% while ensuring structural rigidity meets mechanical requirements during high-speed cornering. In terms of dynamic stability studies, Uddin has revealed changes in the aerodynamic characteristics of racing cars under crosswind conditions through multiphase flow simulations. The study found that optimizing the side box airflow design can effectively reduce crosswind interference and maintain aerodynamic balance in corners. Bardford proposes innovative solutions from a flow control perspective, where the active airflow control technology studied can adjust the angle of the flaps in real-time to respond to different cornering conditions, significantly enhancing steering stability. The rear wing and diffuser work together to generate downforce at high speeds, increasing tire grip.

Rear Wing Design: A high-angle rear wing can increase downforce, but it also generates greater aerodynamic drag. Therefore, engineers employ a Variable Rear Wing (DRS) system to reduce drag on straights and improve top speed [3].

Diffuser Optimization: The diffuser accelerates airflow beneath the chassis, leveraging the Venturi effect to create a low-pressure area, thus enhancing ground effect. Research indicates that optimizing the geometry of the diffuser can increase downforce by 20-30% [5].

4. Cooling and heat management

Race car engines and braking systems generate a significant amount of heat, requiring efficient thermal management. Barford indicates that fluid dynamics optimize the design of cooling ducts to ensure sufficient airflow without compromising aerodynamics [6]. CFD simulations assist in determining the placement of radiators and vents to minimize drag and maximize heat dissipation. Therefore, engineers must optimize the cooling airflow paths to minimize the impact on aerodynamic performance.

Radiator airflow management: The study shows that through CFD simulations, optimizing the positions of the radiator's intake and exhaust can reduce airflow separation and improve overall efficiency.

Brake cooling optimization: The design of the brake ducts must ensure adequate cooling airflow while avoiding disruption of the laminar flow around the vehicle body.

DOI: 10.54254/2753-8818/2025.GL25551

5. Future trends: active aerodynamics and AI optimization

5.1. Intelligent development of active aerodynamic systems

Future race car designs will increasingly incorporate intelligent active aerodynamic systems that can sense the car's status and external environment in real time, automatically adjusting wing angles, diffuser shapes, and other aerodynamic components. According to research published in the journal, such adaptive systems can significantly enhance the performance of racing cars under various track conditions while reducing the burden on drivers to manually adjust settings [5].

5.2. The integration of Computational Fluid Dynamics (CFD) and artificial intelligence

The article points out that future CFD simulations will be deeply integrated with artificial intelligence technologies to achieve faster and more accurate aerodynamic analysis [7]. Machine learning algorithms can predict the optimal aerodynamic configurations based on historical data and real-time sensor information, greatly shortening design cycles and improving design quality. This integration will enable teams to test more design options in a virtual environment before conducting actual wind tunnel tests.

5.3. Synergistic optimization of energy efficiency and thermal management

With the emergence of hybrid and fully electric racing cars, exemplified by Formula E, energy management and thermodynamic efficiency have become central concerns. Literature indicates that the battery and motor systems in electric racing cars exhibit high sensitivity to temperature. Consequently, the application of fluid dynamics extends beyond external aerodynamic design; it also necessitates the optimization of internal cooling airflow distribution. For example, by simulating the fluid flow around battery packs using CFD, more efficient heat dissipation channels can be designed, thereby extending the endurance during high-power output.

At the same time, some studies mention the combination of waste heat recovery technologies and aerodynamics. Future race cars may utilize exhaust or battery waste heat to adjust local airflow characteristics (for instance, by heating the wake to reduce turbulent interference behind the car), thereby gaining a tactical advantage during races.

5.4. The reshaping of race car design by sustainable technologies

Tighter environmental regulations have prompted motorsport to rethink its technological route. Existing literature suggests that the increasing utilization of biofuels and synthetic fuels will alter the fluid characteristics within the engine combustion chamber, thereby necessitating a redesign of the intake and fuel injection systems. Moreover, the incorporation of lightweight materials, such as carbon fiber reinforced polymers, requires optimization in conjunction with aerodynamic performance. This is crucial to prevent potentially uncontrollable airflow separation, which can arise from variations in material stiffness.

Another trend is the rise of 'green aerodynamics.' For instance, some studies explore the use of surface microstructures (similar to shark skin texture) to reduce turbulent friction drag, a technology that can enhance efficiency without requiring additional energy input, aligning with sustainability goals.

DOI: 10.54254/2753-8818/2025.GL25551

6. Conclusion

This study confirms that fluid dynamics is fundamental to the optimization of racing car performance across multiple domains. Aerodynamic design strategies such as drag reduction and downforce enhancement are shown to directly affect speed, stability, and cornering capability. Techniques like boundary layer control, surface microstructures, and wake management significantly reduce drag, while optimized diffuser and wing configurations improve downforce and maintain balance during high-speed turns.

Cooling and thermal management systems, when integrated with aerodynamic considerations, help prevent performance degradation due to overheating, particularly in critical components like brakes and radiators. Looking ahead, the integration of intelligent active aerodynamic systems and advanced CFD simulations supported by AI represents a key direction for development. These technologies promise faster iteration cycles, better adaptability to real-time race conditions, and improved design efficiency.

Moreover, sustainability is becoming an essential factor, with emerging technologies focusing on reducing environmental impact through lightweight materials, waste heat recovery, and friction-reducing microstructures. As racing cars evolve, fluid dynamics will continue to drive innovations that balance performance with energy efficiency and adaptability.

References

[1] Uddin, M., & Olkhovskyi, N. (2024). Computational Fluid Dynamics Analyses on How Aerodynamic Rule Changes Impact the Performance of a NASCAR Xfinity Racing Series Racecar. Vehicles, 6(3), 1545–1570. https: //doi.org/10.3390/vehicles6030073

[2] Peri, D., & Di Mascio, A. (2024). Role of the front wing/wheel setting-up on the optimal cornering performances of a Formula 1 car. Proceedings of the Institution of Mechanical Engineers. Part D, Journal of Automobile Engineering, 238(10–11), 2993–3006. https: //doi.org/10.1177/09544070231183757

[3] Laguna-Canales, A. S., Urriolagoitia-Sosa, G., Romero-Ángeles, B., Martinez-Mondragon, M., García-Laguna, M. A., Yparrea-Arreola, R. I., … Urriolagoitia-Calderón, G. M. (2024). Numerical Evaluation of the Effectiveness of the Use of Endplates in Front Wings in Formula One Cars under Multiple Track Operating Conditions. Fluids (Basel), 9(10), 232-. https: //doi.org/10.3390/fluids9100232

[4] Bang, C. S., Rana, Z. A., Könözsy, L., Marchante Rodriguez, V., & Temple, C. (2022). Numerical Investigation and Fluid-Structure Interaction (FSI) Analysis on a Double-Element Simplified Formula One (F1) Composite Wing in the Presence of Ground Effect. Fluids (Basel), 7(2), 85-. https: //doi.org/10.3390/fluids7020085

[5] Roberts, L. S., Correia, J., Finnis, M. V., & Knowles, K. (2016). Aerodynamic characteristics of a wing-and-flap configuration in ground effect and yaw. Proceedings of the Institution of Mechanical Engineers. Part D, Journal of Automobile Engineering, 230(6), 841–854. https: //doi.org/10.1177/0954407015596274

[6] Bradford, J., Montomoli, F., & D'Ammaro, A. (2014). Uncertainty quantification and race car aerodynamics. Proceedings of the Institution of Mechanical Engineers. Part D, Journal of Automobile Engineering, 228(4), 403–411. https: //doi.org/10.1177/0954407013514396

[7] Castellini, M., Barbanera, M., Scungio, M., & Arpino, F. (2020). Numerical and experimental analysis of turbulent fluid flow around latest generation cycling frame. International Journal of Computational Methods and Experimental Measurements, 8(4), 355–366. https: //doi.org/10.2495/CMEM-V8-N4-355-366