Proceedings of CONF-APMM 2025 Symposium: Simulation and Theory of Differential-Integral Equation in Applied Physics
DOI: 10.54254/2753-8818/2025.DL27670

Gravitational Wave Detection via Advanced Laser Interferometry

Jiankai Zhang

Physics Department, Durham University, Durham, United Kingdom
plhs27@durham.ac.uk

Abstract. Advanced laser interferometry has revolutionized gravitational wave astronomy,, enabling the detection of spacetime distortions with unprecedented precision. This paper explores the fundamental principles and technological advancements underpinning this breakthrough, with a particular focus on the role of Nd:YAG lasers in generating coherent 1064 nm radiation through stimulated emission. This paper elaborate on the interferometric techniques employed to measure gravitational wave- induced strain, including Fabry-P´erot cavities that extend effective arm lengths to 1,120 km and achieve timing precision at the attosecond scale. Key noise miti-gation strategies are systematically discussed, such as squeezed vacuum injection and thermal noise control. These approaches play critical roles: squeezed vacuum injection enables the surpassing of the standard quantum limit, while thermal noise control maintains mirror stability at the sub-nanometer level. The paper also presents landmark detections, including the binary black hole merger GW150914 and the neutron star collision GW170817, which validated general relativity and opened the era of multi-messenger astronomy. Additionally, future prospects are outlined, encompassing third-generation ground-based detectors (e.g., the Einstein Telescope) and space-based missions (such as the Laser Interferometer Space Antenna, LISA). These advancements promise to probe primordial grav- itational waves, test extreme gravity regimes, and uncover new astrophysical phenomena, solidifying laser interferometry as a cornerstone of modern obser-vational astronomy.

Keywords: Gravitational waves, Laser interferometry, Nd:YAG lasers, Quantum noise, Multi-messenger astronomy

1. Introduction

A laser (Light Amplification by Stimulated Emission of Radiation) generates coherent electromagnetic radiation through quantum amplification within a gain medium. First demonstrated in 1960, lasers leverage stimulated emission in materials like ruby crystals or Nd: YAG, where population-inverted atomic states emit phase-synchronized photons when triggered by incident light [1-2]. This process produces light with three unparalleled characteristics: spatial coherence (manifested as collimated, diffraction-limited beams), temporal coherence (stable inter-phase relationships over time), and monochromaticity (spectral bandwidths of < 1 kHz for precision-stabilized systems) [3]. These properties enable applications from precision metrology to

© 2026 The Authors. This is an open access article distributed under the terms of the Creative Commons Attribution License 4.0 (https://creativecommons.org/licenses/by/4.0/).

DOI: 10.54254/2753-8818/2025.DL27670

telecommunications, fundamentally reliant on the laser's unique capacity to maintain phase stability over kilometer-scale distances. Gravitational wave astronomy emerged from the innovative adaptation of laser inter- ferometry to measure spacetime curvature. Rainer Weiss's 1972 proposal established that passing gravitational waves induce differential path-length changes (ΔL) in perpendicular interferometer arms, detectable via laser phase shifts [4]. The corresponding relational expression is as follows:

$$\Delta\phi = \frac{4\pi}{\lambda}\Delta L \tag{1}$$

Drever's incorporation of Fabry-P′erot cavities extended effective arm lengths beyond physical dimensions, while Caves's quantum noise theory addressed fundamental sensitivity limits [5-6]. The 2015 detection of GW150914 by Ad- vanced LIGO validated these methodologies, achieving a strain sensitivity of 10-21 through stabilized 1064 nm Nd: YAG lasers [7]. Critically, seismic noise at frequencies below 10 Hz imposes observational constraints, necessitating advanced laser architectures for next-generation observatories [8].

2. Structure and identities of laser device

As shown in equations 1, a basic laser device included a pump that provided the input energy, a gain medium to let stimulated emission occur, a 100% reflect rate mirror, and a mirror that had a reflect rate less than 100%. The electrons in the gain medium(usually gases or crystals) absorb photons from the pump, which leads to stimulated emission and spontaneous emission, as illustrated in Equations 2, 3, and 4. The rate of change of populations N1 and N2 in those processes can be modeled as:

$$\frac{dN_1}{dt} = -B_{12}N_1\rho(v)(Abamptlon) \tag{2}$$

$$\frac{dN_2}{dt} = -B_{21}N_{20}(v)(\text{Stimulated emiesion}) \tag{3}$$

$$\frac{dN_2}{dt} = -A_{21}N_2\,(Spontameonsemlesion) \tag{4}$$

Where the physical quantities are defined as follows: N1 and N2 [atoms/m^3] represent the population densities in the ground state (E1) and excited state (E2) respectively. B12 [m^3/(J·s2)] is the Einstein absorption coefficient, quan- tifying the probability per unit spectral energy density for transitions from E1 to E2. B21 [m^3/(J·s2)] is the Einstein stimulated emission coefficient, giving the induced emission probability under radiation at frequency ν . A21 [s-1] is the Einstein spontaneous emission coefficient, representing the natural decay rate of excited atoms. ρ(ν) [J·s/m^3] denotes the spectral energy density of the electromagnetic field at the transition frequency ν = (E2 - E1)/h, where h is Planck's constant. The negative signs in the equations indicate population depletion processes: absorption reduces N1, while both emission processes deplete N2. These equations form the foundation for understanding laser dynamics and light-matter interactions in quantum optics. The Einstein relations establish fundamental connections between the coefficients governing absorption, stimulated emission, and spontaneous emission processes. The first key relation connects the spontaneous emission coefficient A21 to the stimulated emission coefficient B21 through the equation:

DOI: 10.54254/2753-8818/2025.DL27670

$$\frac{A_{21}}{B_{21}} = \frac{8\pi h\nu^3}{c^3} \tag{5}$$

where h is Planck's constant, ν is the transition frequency, and c is the speed of light. This relation reveals that spontaneous emission becomes increasingly dominant at higher frequencies, owing to the cubic dependence on ν.

A second crucial relation connects the absorption coefficient B12 to the stimulated emission coefficient B21 through the degeneracies g1 and g2 of the respective energy levels:

$$g1B12 = g2B21 \tag{6}$$

This equality illustrates how the transition probabilities between states depend on their statistical weights. For non-degenerate systems where g1 = g2, the coefficients B12 and B21 become identical. Under thermal equilibrium conditions, these coefficients must satisfy the detailed balance equation:

$$B12\rho(\nu)N1 = B21\rho(\nu)N2 + A21N2 \tag{7}$$

where ρ(ν) represents the spectral energy density of the radiation field, and N1 and N2 denote the population densities of the lower and upper states, re-spectively. This balance equation physically expresses the equilibrium condition where the rate of upward transitions (absorption) equals the combined rate of downward transitions (stimulated and spontaneous emission).

3. Laser system operation

Nd:YAG lasers operate via optical pumping of neodymium ions (Nd^{3+}) embedded in yttrium aluminum garnet (YAG) crystals, using 808 nm diode arrays [9]. The pumping process excites ions to the 4 F3/2 metastable state, creating population inversion for 1064 nm photon generation through stimulated emission. The laser resonator design incorporates high-reflectivity mirrors (>99.97%), which sustain the optical feedback necessary for coherent light amplification.

4. Interferometric detection

The interferometer splits the laser beam at a fused silica beamsplitter, directing the resulting two beams along 4-km perpendicular vacuum arms maintained below 10-9 torr [10]. Each arm functions as a Fabry-P′erot cavity with finesse F = 450, which stores photons for 1 ms (equivalent to 70 round trips) to extend the effective optical path length to 1,120 km. Gravitational waves induce spacetime strain h = ΔL/L in the 10-23 - 10-21 range, creating differential arm length changes ΔL ≥ 10-18 m. This produces measurable phase differences Δϕ in recombining beams, detected via homodyne interferometry with 10-attosecond timing precision—enabling the system to resolve displacements smaller than 0.1 nanometers [11].

5. Noise mitigation

Quantum shot noise is suppressed by 4.7 dB (factor of 3) through squeezed vac- uum injection from optical parametric oscillators, compressing photon-counting uncertainty below the standard quantum limit [12]. The squeezed light source uses magnesium-doped lithium niobate crystals to generate correlated photon pairs. Thermal noise control employs CO_2 laser surface heating to compensate thermal lensing in test masses, maintaining mirror curvature within λ/10, !000 RMS (0.1 nm) through real-time adaptive optics [13]. For broader disturbance suppression, the system combines

DOI: 10.54254/2753-8818/2025.DL27670

passive isolation (via multi-stage pendulums) with active feedback loops, effectively damping seismic and thermal noise across the 20-1000 Hz detection band.

6. Detection results

Advanced LIGO achieved design sensitivity of 4×10-24Hz-1/2 in the 20-500 Hz band during O1-O3 observing runs [14]. Its first detection GW150914 exhibited characteristic chirp waveform from a 36MΘ binary black hole merger at z = 0.09, with peak strain h = 1.0 × 10-21 and signal-to-noise ratio 24 [7]. Laser phase modulation tracked the inspiral (0.2 s duration), merger, and ringdown phasesof the merger with high precision, confirming general relativistic predictions within 5% accuracy. Subsequent quantum-enhanced operations, using frequency-dependent squeezing improved low-frequency sensitivity by 50%, enabling detection of GW190521 - a 150MΘ binary black hole merger at z = 0.82 with peak strain 8.7 × 10-22 [15,16]. The neutron star merger GW170817 demonstrated multi-messenger capabili-ties, where 100-second laser phase tracking localized the source to 28 deg2 for electromagnetic counterpart identification [17]. Calibration accuracy reached ±3% in amplitude and ±2 rad in phase through photon calibrator systems and mirror actuation tests [18].

7. Discussion

Gravitational wave detection currently faces multiple methodological constraints. Above 50 Hz, quantum radiation pressure noise limits sensitivity, imposing a fundamental strain (h) ceiling of approximately 10^{-24}. Below 30 Hz, coating thermal noise—caused by Brownian motion in mirror substrates—further degrades performance. Seismic coupling restricts observations at frequencies below 10 Hz, precluding ground-based detectors from detecting supermassive black hole binaries. Additionally, calibration uncertainties introduce ±5% systematic errors in luminosity distance measurements. To address these limitations, significant advancements are planned for the future of gravitational wave astronomy. Third-generation ground-based detectors, such as the Einstein Telescope and Cosmic Explorer, will deploy cryogenic silicon test masses and 10-kilometer arms, aiming to achieve a strain sensitivity of ~10^{-25} For space-based observations, the LISA mission will utilize 2 W Nd:YAG lasers with 2.5-million-kilometer baselines to detect mHz-band signals from binaries with masses exceeding 10^6 solar masses. Quantum non-demolition techniques, which leverage entangled photon states, hold promise for reducing noise by 10 dB beyond the capabilities of squeezed light. Furthermore, topological insulator coatings may decrease thermal noise by 80% through lower mechanical loss, addressing a key low-frequency limitation of current detectors.

8. Conclusion

Laser interferometry has revolutionized our capacity to observe the universe. transforming gravitational waves from a theoretical prediction into a powerful observational tool. At the core of this revolution are precision laser systems that can detect spacetime distortions smaller than one-thousandth the diameter of a proton. The quantum stability of Nd:YAG lasers enables these incredibly precise measurements, allowing scientists to detect cosmic events like colliding black holes and neutron stars across billions of light-years. The development of advanced noise reduction techniques has been pivotal to this success. Methods like squeezed light injection, which manipulates quantum vacuum fluctuations, and power recycling, which boosts laser intensity within the detector, have significantly improved sensitivity. These innovations now allow the detection of

DOI: 10.54254/2753-8818/2025.DL27670

events occurring when the universe was less than half its current age. Sophisticated vibration isolation systems and AI-powered data analysis further help distinguish faint gravitational signals from background noise. Current detectors still face limitations, most notably at low frequencies, where Earth's constant vibrations disrupt measurements. The planned Laser Interferometer Space Antenna (LISA) mission will overcome this by operating in the quiet environment of space, opening new pos- sibilities for studying massive black holes and other low-frequency sources. Future advancements will likely incorporate quantum technologies like frequency- dependent squeezing to push beyond current detection limits, along with ultra- pure mirror materials cooled to near absolute zero to minimize thermal inter-ference.

These technological leaps hold the promise of revealing unprecedented cosmic phenomena. Researchers hope to detect vibrations from the universe's first moments, test Einstein's theories under extreme gravity, and study the mysterious matter inside neutron stars. Gravitational wave astronomy is now joining forces with traditional telescopes and neutrino detectors, creating a more complete picture of violent cosmic events and the structure of the universe itself. As detectors grow increasingly sensitive, they may uncover entirely new classes of astronomical objects and phenomena—continuing to expand the boundaries of our understanding of the cosmos.

References

[1] Maiman, T. H. (1960). Stimulated optical radiation in ruby. Nature, 187(4736), 493-494.
[2] Siegman, A. E. (1986). Lasers. University Science Books.
[3] Saleh, B. E. A. & Teich, M. C. (2007). Fundamentals of Photonics (2nd ed.). Wiley.
[4] Weiss, R. (1972). Electromagnetically coupled broadband gravitational antenna. Quarterly Progress Report (Research Laboratory of Electronics, MIT), 105, 54.
[5] Drever, R. W. P. et al. (1983). Laser phase and frequency stabilization using an optical resonator. Applied Physics B, 31(2), 97-105.
[6] Caves, C. M. (1981). Quantum-mechanical noise in an interferometer. Physical Review D, 23(8), 1693-1708.
[7] Abbott, B. P. et al. (LIGO Scientific Collaboration & Virgo Collabora- tion) (2016). Observation of gravitational waves from a binary black hole merger. Physical Review Letters, 116(6), 061102.
[8] Matichard, F. et al. (2015). Seismic isolation of advanced LIGO. Preci- sion Engineering, 40, 273-286.
[9] Koechner, W. (2006). Solid-State Laser Engineering (6th ed.). Springer.
[10] Vajente, G. et al. (2020). Machine-learning-based optimization for gravitational-wave detectors. Physical Review D, 101(4), 042003.
[11] Saulson, P. R. (1994). The fundamental noise limit of gravitational wave detectors. Physical Review D, 42(8), 2437-2445.
[12] Aasi, J. et al. (LIGO Scientific Collaboration) (2013). Enhanced sensi-tivity of the LIGO gravitational wave detector by using squeezed states of light. Nature Photonics, 7(8), 613-619.
[13] Bassan, M. et al. (2010). Advanced mirror suspension for gravitational wave detectors. Classical and Quantum Gravity, 27(8), 084026.
[14] Abbott, B. P. et al. (LIGO Scientific Collaboration & Virgo Collabora- tion) (2018). GW170104: Observation of a 50-solar-mass binary black hole coalescence. Physical Review Letters, 120(9), 091101.
[15] McCuller, L. et al. (2020). Frequency-dependent squeezing for advanced LIGO. Physical Review Letters, 124(17), 171102.
[16] Abbott, R. et al. (LIGO Scientific Collaboration & Virgo Collaboration) (2020). GW190425: Observation of a compact binary coalescence. Physical Review Letters, 125(10), 101102.
[17] Abbott, B. P. et al. (LIGO Scientific Collaboration & Virgo Collabora- tion) (2017). GW170817: Observation of gravitational waves from a binary neutron star inspiral. The Astrophysical Journal Letters, 848(2), L12.
[18] Karki, S. et al. (2016). Detection of gravitational waves. Review of Scientific Instruments, 87(11), 114503.