Proceedings of CONF-MPCS 2026 Symposium: Theoretic Physics and Plasma Physics
DOI: 10.54254/2753-8818/2026.DL33858

A Fluid Mechanics Analysis of Wind Turbine Blade Designs for Higher Energy Conversion Efficiency

Chenhao He

Maranatha High School, Pasadena, United States
He.Danny@maranathastudents.org

Abstract. From a fluid-mechanics standpoint, this paper explores how blade design affects the efficiency with which a wind turbine converts wind energy into useful power. This study does not explain turbine performance by looking at only one variable. It focuses on several interacting aerodynamic features—airfoil geometry, blade number, twist and pitch, chord distribution, and tip design. The analysis is based on published research and is understood through the basic ideas of fluid mechanics and blade element momentum theory. The main point is that high efficiency does not usually come from pushing one feature as far as possible. It more often comes from a well-matched combination of advantages within the same blade system. In many cases, an efficient blade includes an airfoil with a high lift-to-drag ratio, three blades, proper twist and pitch to keep a good angle of attack. It also needs a chord shape that matches local flow conditions, along with tip features that can reduce induced losses. Overall, the findings indicate that turbine performance depends on how well these important design variables work together, while still meeting practical engineering needs such as stability, manufacturability, and drag control.

Keywords: wind turbine blade design, energy conversion efficiency, fluid mechanics, aerodynamic optimization, blade element momentum theory

1. Introduction

Wind energy has become a central component of low-carbon electricity systems, and for that reason improving turbine efficiency remains a practical engineering priority. Among the factors that shape performance, blade design is the most important, since it directly influences momentum transfer, local pressure gradients, and the balance between lift and drag as kinetic energy is converted into power. On that basis, this study treats the problem principally as one of fluid mechanics and aerodynamic efficiency rather than of energy policy.

Across the existing literature, a wide range of design variables has been examined, including airfoil profile, blade number, twist and pitch angle, chord distribution, and tip configuration. As the review evidence indicates, each variable can shift aerodynamic behavior in materially relevant ways [1-3]. However, the evidence is often organized around single parameters, so the literature offers too little integrated discussion of which combination of blade features is likely to deliver the highest efficiency under fluid-mechanics criteria.

© 2026 The Authors. This is an open access article distributed under the terms of the Creative Commons Attribution License 4.0 (https://creativecommons.org/licenses/by/4.0/).

DOI: 10.54254/2753-8818/2026.DL33858

This paper focuses on one main question: which wind turbine blade design is most effective for improving energy conversion efficiency from a fluid-mechanics perspective? To answer this question, the study uses a comparative analysis based on existing research and guided by theory. Its main framework comes from fluid mechanics and blade element momentum theory [4]. The rest of the paper is organized in a clear way. Section 2 reviews earlier studies, Section 3 explains the method, Section 4 presents the analysis, and Section 5 gives the implications, limitations, and final conclusion.

2. Aerodynamic factors in wind turbine blade design

At the most basic level, wind turbine efficiency depends on how effectively a blade turns the energy of the incoming flow into useful rotational motion. Blade design has therefore been treated in earlier research not as a single choice, but as a set of aerodynamic variables that shape lift production, drag control, wake development, and overall performance. The variables discussed most frequently in this study are airfoil shape, blade number, twist and pitch, chord distribution, and tip configuration.

One important area of research focuses on airfoil geometry and how it affects the lift-to-drag ratio. From existing studies on blade profiles and aerodynamic optimization, it is now well established that airfoil selection has a direct, significant impact on pressure distribution, boundary-layer development, and flow separation resistance, all of which are critical for energy-conversion efficiency. Hence, the literature shows sustained interest in new airfoil and blade-design approaches [1, 3]. In contrast, other studies evaluate performance through profile evaluation and shape optimization [5, 6]. When considered together, these approaches naturally lead to a clear and important conclusion: an efficient blade should not simply perform well at a single narrowly defined operating point, but must have an airfoil that behaves aerodynamically favorably under realistic operating conditions.

A second cluster of studies systematically and clearly examines the geometric distribution of blade loading, namely blade number, twist, pitch, chord variation, and taper, and thereby establishes a very important general pattern: higher efficiency is not obtained by simply maximizing energy capture, since increases in extraction can be offset by greater drag, higher structural loads, and worse off-design performance. Specifically, one paper approaches the problem from an aero structural optimization perspective [2], while another considers morphing blades as a means of adapting aerodynamic response [7]. Both are valuable because they go beyond considering isolated variables. That said, it is also fair to note that most studies in this cluster optimize performance within a single design framework, rather than comparing combinations of design choices in a more comprehensive manner.

Tip design constitutes another important theme, since induced losses near the blade tip can significantly limit power extraction. Research on swept blades, winglets, and curved tips suggests that, when integrated well with the rest of the blade geometry, such modifications may reduce tip loss and improve wake behavior [8-11]. However, the literature is still somewhat fragmented. Many studies test one variable, or one innovation, at a time; as a result, there is still too little integrated judgment about which combination of blade-design variables is most efficient from a fluid-mechanics perspective. That gap leads directly to the methodological approach adopted in this paper.

3. Comparative analytical framework and evaluation criteria

This paper uses a literature-based and theory-driven method. It is not an experimental study. Instead, it is a qualitative analysis that answers the research question by comparing the main wind turbine

DOI: 10.54254/2753-8818/2026.DL33858

blade design variables discussed in earlier studies.

The study is built on fluid mechanics, aerodynamic principles, and blade element momentum (BEM) theory. BEM is especially useful here as an analytical framework because it links local blade geometry to lift, drag, angle of attack, induced effects, and power extraction in rotating flow systems [4].

This paper presents a study of horizontal-axis wind turbine blades and systematically compares five important design variables: airfoil geometry, blade number, twist and pitch, chord distribution, and tip design, with the rationale being clear: these variables are commonly treated in the literature and all have a direct bearing on aerodynamic performance.

To compare them fairly, a common evaluative framework is used. Included within that framework are lift, drag, the lift-to-drag ratio, angle of attack, tip-speed ratio, power coefficient, tip loss, flow separation, aerodynamic stability, and practical manufacturability. From there, the analysis proceeds in three steps: first, the key variables emphasized in earlier research are identified; next, their aerodynamic effects are comparable; finally, attention turns to which combinations are most consistently associated with higher energy - conversion efficiency.

Given the research question, this method is appropriate because the task is comparative and explanatory rather than experimental. It cannot replace original testing, but it does an excellent job of bringing together results from different studies into a coherent fluid-mechanics analysis, thus naturally leading to a theory-based conclusion about efficient blade design.

4. Comparative analysis of blade-design variables and efficiency implications

Viewed alongside the literature review and the theory-driven method, the analysis indicates that wind-turbine efficiency is not determined by any single blade variable taken on its own. More decisive is the interaction among design features, which together shape lift, drag, angle of attack, and induced loss. Across the studies reviewed here, the better-performing designs are generally those that combine favorable airfoil behavior, balanced rotational characteristics, coherent loading distribution, and reduced tip loss.

4.1. Airfoil shape and aerodynamic efficiency

The evidence points first to airfoil geometry as one of the clearest determinants of blade performance, largely because it governs both the lift-to-drag ratio and the onset of flow separation. A high-performing airfoil is not simply one that produces lift, but one that can maintain useful lift while keeping drag within reasonable limits under practical operating conditions. Comparative reading of profile studies and design reviews suggests that refined airfoil shapes usually support better pressure distribution and more stable energy extraction than less optimized profiles [1, 5, 6]. In that sense, efficient blade design begins with an airfoil that is aerodynamically robust rather than merely adequate.

4.2. Blade number and rotational performance

Blade number, by contrast, shapes the compromise among torque generation, drag penalty, and rotational smoothness. Too few blades may reduce torque and weaken operational stability; too many, meanwhile, tend to increase drag and limit rotational efficiency. From an aerodynamic point of view, the three-blade design seems to work best most consistently. It provides a reasonable

DOI: 10.54254/2753-8818/2026.DL33858

balance between power extraction, stability, and practical operation. This conclusion is also broadly consistent with design reviews such as [3].

4.3. Twist and pitch distribution

Twist and pitch are important for another reason. The local flow angle keeps changing from the root of the blade to the tip. If the geometry is not adjusted properly, some parts of the blade will no longer stay at a favorable angle of attack. When that happens, drag can increase and flow separation may occur earlier. The comparison therefore suggests that efficient blades require twist and pitch distributions capable of maintaining effective aerodynamic loading from root to tip. This idea is also supported by studies on adaptive and optimized blade forms [2, 7].

4.4. Chord distribution and blade taper

Chord distribution is also important for blade efficiency, since different sections of the blade do not produce the same amount of lift and torque. A wider root can help sustain structural and aerodynamic loading, whereas a tapered outer region tends to reduce unnecessary drag and improve the spanwise distribution of force. In fluid-mechanical terms, then, higher performance is associated not with a uniform planform, but with a chord distribution matched to local flow behavior across the blade span.

4.5. Tip design and the reduction of aerodynamic losses

Finally, tip design remains important because the blade tip is a major source of induced loss and vortex formation. Winglets, swept tips, and curved tips matter not because they guarantee universal improvement, but because, when integrated properly with the overall blade geometry, they can reduce tip loss and improve wake behavior [8-11]. Efficiency improves, therefore, when tip-induced losses are treated as a deliberate design problem rather than a secondary detail.

Taken as a whole, the analysis suggests that the most effective wind-turbine blade design is usually associated with an optimized combination: an aerodynamically strong airfoil, a three-blade configuration, suitable twist and pitch distribution, appropriate chord taper, and tip features that reduce induced losses. This finding provides the basis for the discussion that follows.

5. Conclusion

The findings in Section 4 are consistent with basic fluid-mechanics principles, so their aerodynamic logic is fairly clear. A high lift-to-drag ratio is important because useful torque can only be maintained if the blade generates sufficient aerodynamic force without excessive drag, and hence twist is just as necessary: since the relative flow angle changes from the root to the tip, a blade without geometric adjustment would not maintain a favorable angle of attack along its span. For the same reason, tip design is far from trivial. Around the tip, pressure equalization leads to vortices and therefore induced losses, while an appropriately chosen blade number helps keep the loading more uniform without adding undue drag. Thus, the design combination presented in this paper is not arbitrary. It is the result of careful consideration of how all elements form a coherent, optimized aerodynamic system.

These findings have both theoretical and practical implications. On the theoretical side, they suggest that blade efficiency should not be explained by looking at each design variable separately. Instead, it should be understood as the result of several design features working together. From an

DOI: 10.54254/2753-8818/2026.DL33858

engineering point of view, they support that blade optimization should focus on creating a coordinated aerodynamic design, rather than improving one feature too much while weakening the others. At the same time, however, the aerodynamically best-performing design will not automatically be the best option in every real-world context. Structural strength, manufacturability, material limits, cost, noise, maintenance requirements, and scale-specific operating conditions may all shape the final design choice.

Even so, this paper has clear limitations. It does not include original experiments, CFD simulations, or wind-tunnel validation, so the comparative conclusions cannot be tested here under a single unified set of operating conditions. In addition, the studies brought into comparison were conducted with different design aims, turbine scales, and analytical contexts. The conclusion is therefore theoretically informative and comparatively well supported, but it should not be treated as universally valid.

Overall, the paper answers the research question in the following way: from a fluid-mechanics perspective, the most efficient wind-turbine blade design is usually one that combines an aerodynamically efficient airfoil, a three-blade arrangement, optimized twist and pitch, suitable chord taper, and tip features that reduce induced loss. This does not mean that one universally optimal blade exists for all turbines. It does, however, point to the most robust aerodynamic direction for improving energy conversion efficiency, while still recognizing the structural and economic constraints that shape final engineering decisions.

References

[1] Krishnan, A., Al-Obaidi, A. S. M., & Hao, L. C. (2023). A comprehensive review of innovative wind turbine airfoil and blade designs: Toward enhanced efficiency and sustainability. Sustainable Energy Technologies and Assessments, 60, 103511. https: //doi.org/10.1016/j.seta.2023.103511

[2] Batay, S., Baidullayeva, A., Zhao, Y., Wei, D., Baigarina, A., Sarsenov, E., & Shabdan, Y. (2024). Aero structural design optimization of wind turbine blades. Processes, 12(1), 22. https: //doi.org/10.3390/pr12010022

[3] Zha, R., Wu, S., Cai, C., Liu, X., Wang, D., Peng, C., Feng, X., Chen, Q., Zhong, X., & Li, Q. (2025). A review on performance calculation and design methodologies for horizontal-axis wind turbine blades. Energies, 18(2), 435. https: //doi.org/10.3390/en18020435

[4] Ledoux, J., Riffo, S., & Salomon, J. (2021). Analysis of the blade element momentum theory. SIAM Journal on Applied Mathematics, 81(6), 2596–2621. https: //doi.org/10.1137/20M133542X

[5] Erkan, O., Özkan, M., Karakoç, T. H., Garrett, S. J., & Thomas, P. J. (2020). Investigation of aerodynamic performance characteristics of a wind-turbine-blade profile using the finite-volume method. Renewable Energy, 161, 1359–1367. https: //doi.org/10.1016/j.renene.2020.07.138

[6] Lee, H. M., & Kwon, O. J. (2020). Performance improvement of horizontal axis wind turbines by aerodynamic shape optimization including aeroelastic deformation. Renewable Energy, 147(1), 2128–2140. https: //doi.org/10.1016/j.renene.2019.09.125

[7] Akhter, M. Z., Ali, A. R., Jawahar, H. K., Omar, F. K., & Elnajjar, E. (2023). Performance enhancement of small-scale wind turbine featuring morphing blades. Energy, 278, 127772. https: //doi.org/10.1016/j.energy.2023.127772

[8] Kaya, M. N., Kose, F., Ingham, D., Ma, L., & Pourkashanian, M. (2018). Aerodynamic performance of a horizontal axis wind turbine with forward and backward swept blades. Journal of Wind Engineering and Industrial Aerodynamics, 176, 166–173. https: //doi.org/10.1016/j.jweia.2018.03.023

[9] Khalafallah, M. G., Ahmed, A. M., & Emam, M. K. (2019). The effect of using winglets to enhance the performance of swept blades of a horizontal axis wind turbine. Advances in Mechanical Engineering, 11(9), 1687814019878312. https: //doi.org/10.1177/1687814019878312

[10] Mourad, M. G., Shahin, I., Ayad, S. S., Abdellatif, O. E., & Mekhail, T. A. (2020). Effect of winglet geometry on horizontal axis wind turbine performance. Engineering Reports, 2(1), e12101. https: //doi.org/10.1002/eng2.12101

[11] Madsen, M. H. Aa., Zahle, F., González Horcas, S., Barlas, T. K., & Sørensen, N. N. (2022). CFD-based curved tip shape design for wind turbine blades. Wind Energy Science, 7(4), 1471–1501. https: //doi.org/10.5194/wes-7-1471-2022